



## **IPSO LIGHT COMMERCIAL SINGLE WASHERS, DRYERS AND STACKED UNITS**

**ILC 98 Washer - 9.5KG**

**ILC 98 Dryer - 9.5KG**

**ILC 98 Washer/Dryer Stack - 9.5KG**

**ILC 98 Dryer/Dryer Stack - 9.5KG**

**Large Drum  
Size**

**Tilted  
Control Panels**

**Eco  
Option**

### **KEY FEATURES**

- ▶ Tilted control panels increase ease of use & visibility
- ▶ 20% increase in drum size
- ▶ Eco option for smaller loads
- ▶ WRAS Approved category 5
- ▶ Pre-programmed cycles for ease of selection
- ▶ Complies with CQC requirements
- ▶ Dynamic balancing and reduced suspension
- ▶ Coin-Op, Manual
- ▶ Gas or Electric

### **DIMENSIONS**

#### **ILC 98 Washer**

Width (mm): 683  
Depth (mm): 744  
Height (mm): 1121

#### **ILC 98 Dryer**

Width (mm): 683  
Depth (mm): 711  
Height (mm): 1121

#### **ILC 98 Washer/ Dryer Stack**

Width (mm): 683  
Depth (mm): 744  
Height (mm): 1994

#### **ILC 98 Dryer/ Dryer Stack**

Width (mm): 683  
Depth (mm): 711  
Height (mm): 1994

**Alliance**<sup>™</sup>  
Laundry Systems

**IPSO LIGHT COMMERCIAL SPECIFICATIONS**

		<b>ILC 98 WASHER</b>	<b>ILC 98 DRYER</b>	<b>ILC 98 WASHER/ DRYER STACK</b>	<b>ILC 98 DRYER/ DRYER STACK</b>
Capacity	kg	9.5	9.5	9.5/9.5	9.5
Height	mm	1121	1121	1994	1194
Width	mm	683	683	683	683
Depth	mm	744	711	744	711
Net Weight	kg	122	68	177	125
Drum Volume	litres	97	201	97/201	201/201
G Force	G	440		440	
Microprocessor Control		Y	Y	Y	Y
Free Standing		Y	Y	Y	Y
No. of Water Connections	Cold/Hot	1/1		1/1	
Water Connection Size	BSP	3/4		3/4	
Exhaust Diameter	mm ; in		102 ; 4"	102 ; 4"	(2 x) 102 ; 4"
Make-Up Air	m <sup>2</sup> ; in <sup>2</sup>		0.013 ; 20	0.013 ; 20	0.026 ; 40
Airflow	m <sup>3</sup> /min ; ft <sup>3</sup> /min		5.1 ; 180	5.1 ; 180	(2 x) 5.1 ; 180
Drain Connection: Pump standpipe	mm / in	50 / 2		50 / 2	
Drain Valve	mm / in	50 / 2		50 / 2	
Gas Rating	kW ; BTU		5.9 ; 20,000	5.9 ; 20,000	(2 x) 5.9 ; 20,000
Gas Connection Size	BSP		3/8	3/8	(2 x) 3/8
<b>Electrics</b>					
4.8kw Boiler Fed Washer	Volt/ph/Amp	230/1/10		230/1/10	
Self Heat Washer	Volt/ph/Amp	230/1/25		230/1/25	
Electric Heat Dryer	Volt/ph/Amp		230/1/25	230/1/25	(2 x) 230/1/25
Gas Dryer	Volt/ph/Amp		230/1/10	230/1/10	(2 x) 230/1/10
<b>Optional Electrics</b>					
2.4kw Self Heat Washer	Volt/1ph/Amp	230/1/13		230/1/13	
4.8kw Self Heat Washer	Volt/3ph/Amp	400/3/10		400/3/10	

All specifications subject to change without notice. For full specifications, refer to the 'installation specification sheet'. NOTE: A stack unit requires 2 electrical supplies.