

MAYTAG MDE/ MDG28PN COMMERCIAL TUMBLE DRYER



KEY FEATURES

▶ **MICROPROCESSOR CONTROLS**

Provides simple programming options for owner: including adjustable cycle price, cycle time, diagnostics and vend count.

Easy one-touch cycle selection for customers.

▶ **TURBOVENT DRYER TECHNOLOGY**

Additional blower wheel provides exceptional performance in long vents.

High airflow reduces dry time.

▶ **PORCELAIN-ENAMEL TOP**

Durable finish for high-use environments.

▶ **MAYTAG CONNECT 360 COMPATIBLE**

Delivers real-time machine diagnostic to any tablet, computer or smartphone via the cloud. Management and feedback features offer owners the ultimate in machine control keeping you informed regarding pricing, service and diagnosis from anywhere you have access to the internet.

DIMENSIONS

Width (mm): 686 Depth (mm): 743 Height (mm): 1092




**Simple
Programming**



**Front
Access Panel**



**One-Touch
Cycle Selection**



**Matching
Washer Available**

MAYTAG'S COMMITMENT TO DEPENDABLE QUALITY

For well over 50 years, Maytag® Commercial Laundry has promised and delivered dependability. We create that quality by making durable washers and dryers, built to endure heavy use and last for years. We design our machines to perform reliably and to produce consistent results. Finally, we give our washers and dryers the power to do their jobs thoroughly, cleaning and drying laundry quickly and efficiently—and justifying the trust that has been placed in us for generations.



MAYTAG MDE/MDG28PN COMMERCIAL DRYER MANUAL SPECIFICATIONS

MDE/MDG28PN

Motor		
Single-phase, thermoprotected against overload, auto reset		Yes
Hp	kw	1/2 (.25)
Tumble Speed	rpm	50 + 1
Capacity		
Capacity	cu. ft. (litres)	6.7 (190)
Airflow		
Gas Models	cfm (cmm)	230 (6.5)
Electric Models	cfm (cmm)	215 (6.1)
Sound Level		
Sound Pressure Level	Lpa (Dba)	58
Electrical Requirements (V)		
Electrical Requirements (V)		220-240v/50hz
Breaker/Fuse		
Mde Export Model	amps	25
Mde Export Model	amps	10
Electric Heating Element		
Electric Heating Element	watts	4,600
Gas Rating		
Mdg Model - Btu/Hr (Kcal/Hr.)	watts	20,000 (5,040)
Exhaust Duct Diameter- In (Mm)		4 (100)*
Electronic Burner Ignition		
Mdg Model		Yes
Gas Inlet		
Mdg Model	Inches	3/8 N.P.T
Adjustable Leveling Legs		Yes
Approximate Weight		
Crated	lbs. (kg) electric/gas	160 (73)/113 (74)
Uncrated	lbs. (kg) electric/gas	147 (67)/150 (68)
Dimensions		
Width-In	mm	27 (686)
Depth-In	mm	29 (737)
Height-In	mm	45.75 (1,162)
Door Opening Diameter-In	mm	18.25 (464)
Optional Plinth Adds		
Height-In	mm	2.75 (70)

*Use 4" (100 mm) diameter rigid aluminum or galvanized steel duct. Never use plastic, non-metal or combustible duct.
 **Includes height of metercase.
 See specific instructions for proper installation.
 Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

MAXIMUM EXHAUST DUCT LENGTH PER NUMBER OF TURNS

Number Of 90° Turns	Rigid Metal Vent	
	Box Hood and Louvered Style	Angled Hood Style
0	135 ft. (41.2 m)	129 ft. (39.3 m)
1	125 ft. (38.1 m)	119 ft. (36.3 m)
2	115 ft. (35.1 m)	109 ft. (33.2 m)
3	106 ft. (32.3 m)	100 ft. (30.5 m)
4	98 ft. (29.9 m)	92 ft. (28.0 m)

Number Of 90° Turns	Flexible Metal Vent	
	Box Hood and Louvered Style	Angled Hood Style
0	76 ft. (23.2 m)	62 ft. (18.9 m)
1	71 ft. (21.6 m)	57 ft. (17.4 m)
2	67 ft. (20.4 m)	53 ft. (16.2 m)
3	65 ft. (19.8 m)	51 ft. (15.6 m)
4	63 ft. (19.2 m)	49 ft. (14.9 m)

