



## SCHULTHESS STARLINE 7720



### DIMENSIONS:

Height: 850mm  
Width: 600mm  
Depth: 670mm

### CAPACITY:

7kg

### IDEAL FOR:



PUBLIC SECTOR



HEALTHCARE

### FEATURES:

- ▶ Large 4.3" colour display
- ▶ Drum vanes for 3D-Washing
- ▶ LED drum lighting
- ▶ Drum capacity: 60 l
- ▶ Spin speed: 1500 rpm
- ▶ G Factor 605
- ▶ Residual moisture 44%
- ▶ Door opening angle 180°
- ▶ Programme progress and remaining time display
- ▶ 24 freely programmable slots
- ▶ ProfiClean programme button
- ▶ Favorites for your 6 favourite programmes
- ▶ 35 profiClean programmes for small commercial businesses, building cleaners and special programmes
- ▶ 40–85 °C disinfection programmes Programme groups Sportswear, Businesswear, Home care, Antibac

### OPTIONS:

- ▶ Hot water connection
- ▶ Programme expansion module with PC interface
- ▶ Coin box interface
- ▶ Machine plinth in chrome steel, H: 35.5 cm
- ▶ Machine plinth with fluff filter drawer, H: 40 cm
- ▶ Drain valve or drain pump
- ▶ Door hinge right or left

**ONECARE<sup>∞</sup>** This machine is eligible for our all inclusive service solution, One Care.

**service  
Master** 

This machine is compatible with our smart laundry solution, serviceMaster

**STARLINE 7720 WASHING MACHINE**

Model with drain pump (P)	7720.1PU
Model with drain valve (V)	7720.1UV
<b>Application features</b>	
Load capacity	7kg
Drum capacity	60l
Spinning speed	1500 rpm
g Factor	605g
Residual moisture <sup>1)</sup>	44%
<b>Structural design</b>	
Footed appliance with work surface	•
Door hinge <sup>3)</sup>	r/l/w
<b>Dimensions</b>	
Height	85cm
Width	60cm
Depth including distance from wall	67cm
Depth with door open (front loader)	110cm
Height (adjustable)	1cm
Weight when empty	90kg
<b>Equipment</b>	
Detergent tank and drum	chrome-nickel steel
Loading opening	34cm / 180°
Automatic door opening	•
Connecting cable	1.6m
Drain:	
– Drain hose with benda, only model (P)	1.5m
– Model with drain pump (P)	21mm
– Model with drain valve (V)	50mm
<b>Electric power and water supply</b>	
Electrical connection	400 V 2N~ / 50Hz / 4.6kW 10A
Voltage / connected loads /fuse	230 V 1N~ / 50Hz / 2.3kW 10A
Water connection	
– Pressure hose G ¾" with fine filter	1.5m
– Can be connected to cold water hot water	cold water/ hot water 70°C
– Water pressure	1-10 bar
<b>Safety and service</b>	
Conforms to the European Machinery Directive	2006/42/EC
Country of origin	Switzerland
Guarantee	1 year
Service by	Schulthess Maschinen AG