



SMEG HOOD TYPE COMMERCIAL DISHWASHER



DIMENSIONS:

Height: 1523mm / Open: 2138mm

Width: 634mm

Depth: 750mm

IDEAL FOR:



HOUSING
ASSOCIATIONS



HEALTHCARE



HOTELS &
HOSPITALITY

FEATURES:

- ▶ Double skinned hood
- ▶ Integral water softener
- ▶ Electronic soft touch controls
- ▶ WRAS approved
- ▶ Auto-dosing chemical
- ▶ Wash pump with "soft start"
- ▶ Thermostop controlled rinse temperature
- ▶ Insulated boiler
- ▶ Auto-start function via hood closure
- ▶ Atmospheric boiler and rinse pump (HTR)

ONECARE[∞]

This machine is eligible for our all inclusive service solution, One Care.

SMEG HOOD TYPE SPECIFICATIONS

Cycle time	min	1
Baskets (x2)	mm	500 x 500
Height	mm	1523 / 2138
Width	mm	634
Depth	mm	750
Baskets per hour		60
Number of programmes		7
Thermo-acoustic insulation		Hood
Rinse aid dispenser		Peristaltic pump with electronic adjustment
Detergent dispenser		Peristaltic pump with electronic adjustment
Wash tank capacity	L	14
Boiler capacity	L	10
Boiler element	kW	9
Wash tank heating element	kW	2.2
Power supply / Total power installed	kW	400 V 3N / 16 A / 9.7 kW / 50 Hz
Wash pump	kW	0.7
Water consumption per cycle	L	3.2
Weight (net/gross)	kg	127kg/136kg
Adjustable feet		Yes
Water connection	BSP	3/4"
Useable loading height	mm	470
Inlet water max temperature	°C	60