



ADC AD-50i 24kg TUMBLE DRYER



MODELS:

ADC AD-50i

DIMENSIONS:

HxWxD: 1870×880×1251mm

CAPACITY:

24kg

IDEAL FOR:



PUBLIC SECTOR



EDUCATION

FEATURES:

- ▶ Variable drum speed
- ▶ Pre-heat system
- ▶ Trans-axial airflow
- ▶ Fully insulated cabinet
- ▶ Double pane door glass
- ▶ Self-cleaning lint screen
- ▶ Direct spark ignition
- ▶ Two-point roller support
- ▶ Simplified inverter drive system
- ▶ Fits through standard 36" door
- ▶ Available in gas & electric
- ▶ Single-phase reversing basket
- ▶ Stainless steel basket and fronts

SYSTEMS:

- "IMC®" intuitive micro control with autodry system
- S.A.F.E

ONECARE^{cc} This machine is eligible for our all inclusive service solution, One Care.

| | | AD-50i | | |
|---------------------------------|-------------------------------|-------------------------------|---------|--|
| Application features | | | | |
| Tumbler Capacity | kg (lb) | 24 | (50) | |
| Tumbler Diameter | cm | 83.18 | | |
| Tumbler Depth | cm | 92.25 | | |
| Tumbler Volume | litres | 518.19 | | |
| Tumbler/Drive Motor | kW | 0.75 | | |
| Blower/Fan Motor | kW | 0.56 | | |
| Door Opening (Diameter) | cm | 68.58 | | |
| Door Sill Height | cm | 74 | | |
| Water connection | | | | |
| S.A.F.E. Water Connection | inches | 3/4 | | |
| Dimensions | | | | |
| Width | mm | 880 | | |
| Depth | mm | 1251 | | |
| Height | mm | 1870 | | |
| Exhaust Connection | inches | 8 | | |
| Connection | | | | |
| GAS | Voltage Available | 120-480V 1,3ø 2,3 50/60 Hz | | |
| | Approximate Net Weight | kg | 298 | |
| | Approximate Shipping Weight | kg | 322 | |
| | Airflow | cfm | 810 | |
| | Heat Input | Btu/hr | 125,000 | |
| | Exhaust Connection (Diameter) | inches | 8 | |
| Inlet Pipe Connection | inches | 1/2 B.S.P.T. (Female) | | |
| ELECTRIC | Voltage Available | 208-480V 1,3ø 2,3,4w 50/60 Hz | | |
| | Approximate Net Weight | kg | 299 | |
| | Approximate Shipping Weight | kg | 324 | |
| | Airflow | cfm | 714 | |
| | Exhaust Connection (Diameter) | inches | 8 | |
| STEAM | Voltage Available | 120-480V 1,3ø 2,3 50/60 Hz | | |
| | Approximate Net Weight | kg | 310 | |
| | Approximate Shipping Weight | kg | 338 | |
| | Airflow | cfm | 767 | |
| Steam Consumption (Max) | kg/hr | 47.62 | | |
| Operating Steam Pressure | bar | 10.34 | | |
| Exhaust Connection (Diameter) | inches | 8 | | |
| Boiler Horsepower (Normal Load) | Bhp | 2.7 | | |
| Supply Connection | inches | 3/4 NPT (Male) | | |

