CAPACITY:



ADC AD-80i 37kg **TUMBLE DRYER**



MODELS: DIMENSIONS:

ADC AD-80i HxWxD: 1980×990×1330mm 37kg

IDEAL FOR: PUBLIC SECTOR

FEATURES:

- ▶ Variable drum speed
- ▶ Pre-heat system
- ▶ Trans-axial airflow
- Fully insulated cabinet
- Double pane door glass
- ▶ Self-cleaning lint screen
- Direct spark ignition
- ▶ Two-point roller support

- Simplified inverter drive system
- Fits through standard 48" door
- Available in gas & electric
- Single-phase reversing basket
- > Stainless steel basket and fronts

SYSTEMS:

- "IMC®" intuitve micro control with autodry system
- S.A.F.E

ONECARE This machine is eligible for our all inclusive service solution, One Care.

			AD-80i		
Application features					
Tumbler Capacity		kg (lb)	37 (80)		
Tumbler Diameter		cm	93.98		
Tumbler Depth		cm	90.01		
Tumbler Volume		litres	624.39		
Tumbler/Drive Motor		kW	0.74		
Blower/Fan Motor		kW	0.56		
Door Opening (Diameter)		cm	79.69		
Door Sill Height		cm	73.66		
Water connection					
S.A.F.E. Water Connection		inches	3/4		
Dimensions					
Width		mm	990		
Depth		mm	1330		
Height		mm	1980		
Exhaust Connection		inches	8		
Connection					
GAS	Voltage Available		120-480V	1,3ø 2,3 50/6	0 Hz
	Approximate Net Weight	kg	318		
	Approximate Shipping Weight	kg	327		
	Airflow	cfm	880		
	Heat Input	Btu/hr	135,000		
	Exhaust Connection (Diameter)	inches	8		
	Inlet Pipe Connection	inches	1/2 B.S.P.T.	(Female)	
ELECTRIC	Voltage Available		208-480V	1,3ø 2,3,4w 5	60/60 Hz
	Approximate Net Weight	kg	322		
	Approximate Shipping Weight	kg	332		
	Airflow	cfm	770		
	Exhaust Connection (Diameter)	inches	8		
			kW	Btu/hr	kcal/hr
_	Oven Size		22	75,067	18,917
	Over 13ize		20.4	69,608	17,541
			18.5	63,125	15,907
STEAM	Voltage Available		120-480V	1,3ø 2,3 50/6	0 Hz
	Approximate Net Weight	kg	377		
	Approximate Shipping Weight	kg	393		
	Airflow	cfm	854		
	Steam Consumption (Max)	kg/hr	63.50		
	Operating Steam Pressure	bar	10.34		
	Exhaust Connection (Diameter)	inches	8		
	Boiler Horsepower (Normal Load)	Bhp	3.6		
	Supply Connection	inches	3/4" NPT (F	emale)	
	Return Connection	inches	2 x 3/4" NF	PT (Male)	







