

SCHULTHESS E2 IRONER RANGE



MODEL:	DIMENSIONS:
G14.25	1.4 Metre x 25cm
G15.35	1.5 Metre x 35cm
G18.35	1.8 Metre x 35cm
G21.35	2.1 Metre x 35cm
G21.50	2.1 Metre x 50cm
G26.35	2.6 Metre x 50cm
G26.50	2.6 Metre x 50cm
G32.50	3.2 Metre x 50cm

SUITABLE FOR:

 [Call us for more info](#)

FEATURES:

- ▶ **Unmatched Finish:**
Achieve smooth results with a specially developed pressure roller. Get gentle care for delicate fabrics with Meta Aramid detaching linen ribbons.
- ▶ **Double Temperature:**
Top temperature control system with dual sensors. Exclusive mechanism prevents fluctuations, halts heating to protect textiles, and reduce energy waste.
- ▶ **Maintenance-Free:**
Padding-free rollers eliminate downtime from rubber peeling.
- ▶ **Strongly Built:**
Robust construction for long-term reliability, with oversized components and premium materials
- ▶ **Mirror Polished Cylinder:**
Seamless cylinders, ensuring optimal ironing results with mirror polishing for a smooth finish.
- ▶ **Patented Titanium-Steel Burner:**
Efficient burner for precise temperature control, boasting easy installation, servicing, and high reliability due to its patented design.
- ▶ **User-Friendly Control Panel**
A user-friendly interface allows personalised features, with smart diagnostics.
- ▶ **Easy Access to Components**
Components are easily accessible for inspection, ensuring smooth maintenance procedures.
- ▶ **Foot Pedal**
Stops roller rotation, leaving hands free to adjust linen during the feeding process.
- ▶ **Steam Extraction**
Air-Blades system provides extra-efficient steam extraction, reducing maintenance frequency.

SKS System efficiently collects steam flow, minimizing heat dispersion and shortening drying times.

ONECARE[∞] This machine is eligible for our all inclusive service solution, One Care.

			G14.25	G15.35	G18.35	G21.35	G26.35
Cylinder Dimensions		mm	1450 x Ø270	1480 x Ø325	1800 x Ø325	2100 x Ø325	2580 x Ø325
Supply Tension *, Electric/Gas/Steam			V.400/3N/50Hz V.230/1/50Hz	V.400/3N/50Hz V.230/1/50Hz	V.400/3N/50Hz V.230/1/50Hz	V.400/3N/50Hz V.230/1/50Hz	V.400/3N/50Hz V.230/1/50Hz
HEATING SOURCE							
Electric	Heating power	kW	12	18	20,7	23,4	29,7
Gas	Thermal power	kW	13,6	22	25,6	27	33,5
	Gas Consumption Nat. Gas	m³/h	1,44	2,26	2,71	2,82	3,53
	Gas Consumption LPG	kg/h	1,05	1,8	2,02	2,2	2,5
Steam	Average Consumption	kg/h	n/a	18	22	26	32
MOTOR(S)							
Electric/Steam		kW	0,27	1	1	1	1
Gas		kW	0,32	1,2	1,2	1,2	1,2
TOTAL POWER							
	Electric	A	V.400/3: 17,8 A	V.400/3: 29 A	V.400/3: 31,5 A	V.400/3: 38 A	V.400/3: 43 A
	Gas/Steam	A	V.230/1: 2,2 A	V.230/1: 5 A	V.230/1: 5 A	V.230/1: 5 A	V.230/1: 5 A
Ironing Speed, Variable		m/min	0,8 3	1,6 5	1,6 5	1,6 5	1,6 5
Steam Extraction		m³/h	280	280	280	280	280
Fumes Extraction		m³/h	100	140	140	140	140
Hourly Production (Recommended Moisture 50%)		kg	25	43	50	56	75
Ironer Dimensions		mm	2010x510x1080	2010x550x1100	2340x550x1100	2640x550x1100	3140x580x1150
Packing Dimensions (W,D,H)		mm	2130x690x1300	2140x730x1560	2490x730x1560	2890x730x1560	3290x730x1560
Weight, Gross/Net		kg	360/310	497/450	540/490	602/548	700/635

* DIFFERENT VOLTAGES AVAILABLE ON REQUEST, PLEASE CONTACT OUR SALES TEAM FOR MORE INFORMATION

			G21.50	G26.50	G32.50
Cylinder Dimensions		mm	2100 x Ø500	2580 x Ø500	3200 x Ø500
Supply Tension *			V.400/3N/50Hz	400/3N/50Hz	V.400/3N/50Hz
HEATING SOURCE					
Electric	Heating Power	kW	45	57	66
Gas	Thermal Power	kW	54	67	95,2
	Gas Consumption Nat. Gas	m³/h	5,7	7	10
	Gas Consumption LPG	kg/h	4,3	5,3	7,5
Steam	Average Consumption	kg/h	50	70	90
MOTOR(S)					
Electric/Steam		kW	1,6	1,6	1,6
Gas		kW	2,7	2,7	2,7
TOTAL POWER					
	Electric	A	69	85	98
	Gas/Steam	A	5	5	5
Ironing Speed, Variable		m/min	1,6 8	1,6 8	1,6 8
Steam Extraction		m³/h	740	740	740
Fumes Extraction		m³/h	1200	1200	1200
Hourly Production (Recommended Moisture 50%)		kg/h kg/h kg/h	75 kg/h el 85 kg/h gas 95 kg/h steam @4bar	95 kg/h el 110 kg/h gas 115 kg/h steam @4bar	120 kg/h el 135 kg/h gas 145 kg/h steam @4bar
Ironer Dimensions		mm	2880x750x1290	3280x750x1290	3880x750x1290
Packing Dimensions (W,D,H)		mm	2990x920x1600	3390x920x1600	4190x920x1600
Weight, Gross/Net		kg	1288/1200	1413/1320	1800/1700

* DIFFERENT VOLTAGES AVAILABLE ON REQUEST, PLEASE CONTACT OUR SALES TEAM FOR MORE INFORMATION