# RCIAL





# **IPSO ILC98 WASHING MACHINE**

#### **DIMENSIONS:**

Height: 1121mm Width: 683mm Depth: 744mm

CAPACITY:

9.5kg

#### **IDEAL FOR:**

| Nh | INDUSTRIAL  | \$ | EDUCATION  |
|----|-------------|----|------------|
| ≏  | HOSPITALITY | ፹  | PUBLIC SEC |
| €  | HEALTHCARE  | €  | VENDED LA  |
|    |             |    |            |

ANIMAL CARE

CTOR

UNDRY

### **FEATURES:**

- Pre-programmed cycles for ease of
- selection
- Enhanced wash options Eco option for smaller loads
- Leak detection feature
- Manual auditing of cycle counts
- Lifetime data history
- Fully updateable firmware for future proofing
- Unique serpentine baffles
- scoop water in
- either direction for enhanced wash action
- Instant door release on
- completion
- Dynamic balancing and
  - re-designed suspension

# **OPTIONS:**

- Sluice option available
- OPL or coin operated
- Self heat or boiler fed
- Pump or gravity drain Auto-dose ready

## **REGULATIONS:**

- WRAS approved category 5
- Complies with CQC requirements
- WTL approved



#### THE COMMERCIAL LAUNDRY EXPERTS.



| ILC98 WASHER                     | ILC 98 WASHER    |  |  |  |
|----------------------------------|------------------|--|--|--|
| Capacity                         | 9.5kg            |  |  |  |
| Height                           | 1121 mm          |  |  |  |
| Width                            | 683 mm           |  |  |  |
| Depth                            | 744 mm           |  |  |  |
| Net Weight                       | 122 kg           |  |  |  |
| Drum Volume                      | 971              |  |  |  |
| G Force                          | 440 G            |  |  |  |
| Microprocessor Control           | Y                |  |  |  |
| Free Standing                    | Y                |  |  |  |
| No. of Water Connections         | 1/1              |  |  |  |
| Water Connection Size            | 3/4 BSP          |  |  |  |
| Exhaust Diameter                 |                  |  |  |  |
| Make-Up Air                      |                  |  |  |  |
| Airflow m3/min ; ft3/min         |                  |  |  |  |
| Drain Connection: Pump standpipe | 50/ 2 mm / in    |  |  |  |
| Drain Valve                      | 50/ 2 mm / in    |  |  |  |
| Gas Rating kW ; BTU              |                  |  |  |  |
| Gas Connection Size              |                  |  |  |  |
| Electrics                        |                  |  |  |  |
| 4.8kw Boiler Fed Washer          | 230 V/1ph/10 Amp |  |  |  |
| Self Heat Washer                 | 230 V/1ph/25 AMP |  |  |  |
| Electric Heat Dryer              |                  |  |  |  |
| Gas Dryer                        |                  |  |  |  |
| Optional Electrics               |                  |  |  |  |
| 2.4kw Self Heat Washer           | 230 V/1ph/13 Amp |  |  |  |
| 4.8kw Self Heat Washer           | 400 V/3ph/10 Amp |  |  |  |