



MAYTAG MH33PN WASHING MACHINE

DIMENSIONS:

Height: 961mm
Width: 686mm
Depth: 732mm

CAPACITY:

9kg

IDEAL FOR:



EDUCATION



HOSPITALITY

FEATURES:

- ▶ Delivers more accurate cycle times and better unbalanced performance
- ▶ A six-point suspension provides better stability
- ▶ Energy-Efficient Cleaning
- ▶ TurboWash™ System's proven high efficiency technology delivers energy savings
- ▶ Duracore Drive System
- ▶ Durable shaft sleeve
- ▶ Designed to eliminate shaft wear
- ▶ Watertight, flexible triple-lip seal with garter spring protecting bearings and life cycle
- ▶ Only uses 40.5l of water per cycle
- ▶ An accelerometer provides an accurate reading of cabinet vibration

OPTIONS:

- ▶ Coin operated models available
- ▶ Stackable with MDE28PN

PROGRAMMES:

- ▶ Clothespin® app by Maytag

With our Clothespin™ app, residents will be able to pay for their laundry using their smartphone, check for available machines, and receive a notification when a cycle is complete. Now they can keep an eye on their laundry from wherever they are, making laundry day a littler easier

ONECARE[∞] This machine is eligible for our all inclusive service solution, One Care.

MAYTAG MHN33PD

Washer Specifications	
Motor	½ (.37)
Variable-Speed, Reversible, Thermoprotected,	Yes
High-Efficiency, Controlled Induction	.09 (.07)
Wash	.54 (.40) hp (kw)
Extract	.054 hp (kw)
Average Energy Consumption Per Cycle	6.7 (190) (kwh)
Capacity	
Cylinder Volume cu. ft. (liters)	31 (88)
Cylinder Diameter in. (mm)	21.6 (547)
Cylinder Depth in. (mm)	13.4 (341)
Water Inlet Hose	
Water Inlet Hose ft. (m)	4 (1.22)
Drain Hose	
Drain Hose ft. (m)	6 (1.83)
Approximate Water Usage	
Average Hot Water Usage, Hot Water Cycle	2.71 (10.26) gallons (liters)
Average Hot Water Usage, Warm Water Cycle	.71 (2.69) gallons (liters)
Average Total Water Usage Per Cycle*	10.71 (40.5) gallons (liters)
Modified Energy Factor (Mefj2)*	2.2
Integrated Water Factor (Iwf)*	3.50
Electrical Rating	
Domestic Model - voltage	220v / 50hz
Breaker / Fuse Min. Requirements	
Domestic Model	13 amps
Wash Speed	40 rpm
Extract Speed - max rpm / max g-forc	1,000 / 300
Water Supply Pressure	
Breaker / Fuse Min. Requirements - psi (bar)	20 – 100 (1 – 8)
Adjustable Leveling Legs	Yes
Color	White
Approximate Weight	
Crated - lbs. (kg)	254 (115)
Uncrated - lbs. (kg)	245 (111)
Dimensions	
Width -in. (mm)	27 (686)
Depth- in. (mm)	28.81 (732)
Height -in. (mm)	37.81 (961)**
Door Opening Diameter -in. (mm)**	14.25 (362)
Ada-Compliant With Optional Pedestal	Yes
Optional Pedestal Add:	
Height -in. (mm)	2.75 (70)

