



MAYTAG MAT20PN TOP-LOAD WASHING MACHINE



DIMENSIONS:

Height: 1255mm
Width: 686mm
Depth: 660mm

CAPACITY:

9kg

IDEAL FOR:



HOSPITALITY



INDUSTRIAL

FEATURES:

- ▶ Sturdy front and side panels
- ▶ Easy-access base
- ▶ Manufactured from high-grade, extra-strength galvanised steel
- ▶ Enhanced design of the triple-lip seal
- ▶ Stainless-steel shaft
- ▶ Premium bearings
- ▶ Powerful ½-HP PSC motor
- ▶ Quad gear transmission
- ▶ Provides optimal wash performance

- ▶ Deep-water wash and rinse cycle options
- ▶ Traditional flex-vane agitator
- ▶ PowerWash® cycle provides more agitation
- ▶ Puts owners in charge of their profits, and provides wash-cycle flexibility to end users
- ▶ Simple, step-by-step customised set-up allows each cycle to be priced individually

OPTIONS:

- ▶ Coin operated models available

ONECARE^{cc}

This machine is eligible for our all inclusive service solution, One Care.

WASHER SPECIFICATIONS

MODEL	MAT20PN
MOTOR SIZE—HP (KW)	1/2 (.37)
EXTRACT SPEED—MAX G-FORCE / MAX RPM	144/700
APPROXIMATE WATER USAGE—GALLONS (LITERS)	
Average total water usage per cycle	16.59 (62.8)
Average hot water usage, warm water cycle	.56 (2.1)
Average hot water usage, hot water cycle	7.03 (26.6)
CAPACITY	
Cylinder volume—cu. ft. (liters)	2.9 (82)
Cylinder diameter—in. (mm)	20.8 (528)
Cylinder depth—in. (mm)	23.8 (605)
DIMENSIONS	
Width—in. (mm)	27 (686)
Depth—in. (mm)	26 (660)
Height—in. (mm)	42-1/2 (1,080)
Lid opening—in. (mm)	17 (432)
CRATED DIMENSIONS	
Width—in. (mm)	29 (737)
Depth—in. (mm)	27.5 (699)
Height—in. (mm)	49 (1,255)
APPROXIMATE WEIGHT	
Uncrated—lbs. (kg)	146 (66.2)
Crated—lbs. (kg)	164 (74.4)
ELECTRICAL REQUIREMENTS	
Electrical rating—voltage/HZ	220–240/50
Breaker/Fuse—amps	10
WATER INLET / HOSE	
Operating pressure PSI (bar)	20–100 (1–8)
Inlet hose length—ft. (m)	6 (1.8)
Drain hose length—ft. (m)	4.2 (1.3)

