



PRIMUS DX LINE TUMBLE DRYERS

MODELS:

DX25
DX34

DIMENSIONS:

HxWxD: 1960×980×1190mm
HxWxD: 1960×980×1350mm

CAPACITY:

25kg
34kg

IDEAL FOR:



VENDED LAUNDRY



INDUSTRIAL



HEALTHCARE



HOSPITALITY



PUBLIC SECTOR

FEATURES:

- ▶ Electrical or Gas heating
- ▶ Large door opening for easy loading and unloading
- ▶ Galvanized drum
- ▶ Axial airflow
- ▶ Large lint filter
- ▶ Controls:
 - Dual Digital Control or OPL Micro
 - Coin operated version: XQ-Control

OPTIONS:

- ▶ Stainless steel drum
- ▶ Coin operated version
- ▶ Reversing drum
- ▶ Residual moisture control Sensodry+® (only with Full OPL Micro):
 - lower energy and utility costs
 - lower linen replacement costs
- ▶ SafeTech™ Fire Suppression System

ONECARE^{cc} This machine is eligible for our all inclusive service solution, One Care.

DX LINE SPECIFICATIONS	DX25	DX34
CAPACITY		
Capacity	25kg	34kg
Drum Volume	530l	634l
Drum Diameter	940 mm	940 mm
AIRFLOW		
Airflow	330 l/s	380 l/s (G 330)
DRYING AVERAGE		
Gas Heating	476 g/min	571 g/min
Electric Heating	390 g/min	521 g/min
MOTOR		
Fan	0,4 kW	0,4 kW
Drive	0,4 kW	0,4 kW
GAS HEATING		
Energy	38,1kW	48,4kW
Energy	130 kBTU/h	165 kBTU/h
Electrical connection	1×100-120V/50-60Hz, 1-3×200-240V/50-60 Hz 3×440-480V/50-60Hz, 3×380-415V/50-60Hz	
Gas Connection	1/2" NPT	1/2" NPT
STEAM HEATING		
Steam Connection	3/4" NPT	3/4" NPT
Electrical Connection	1×100-120V/50-60Hz, 1-3×200-240V/50-60 Hz 3×440-480V/50-60Hz, 3×380-415V/50-60Hz	
High Pressure 6.9 bar	33.29 kW	39.24 kW
High Pressure 6.9 bar	113.6 kBTU/h	113.9 kBTU/h
ELECTRICAL HEATING		
Energy	30 kW	36 kW
Electrical connection	1×200-208V/50-60Hz, 3×200-208V/50-60Hz, 1x 230-240V/50-60Hz, 3x 230-240V/50-60Hz, 3x 380V/50-60Hz, 3x400-415V/50-60Hz, 3x 440V/50-60Hz, 3x 460-480V/50-60Hz	
EXHAUST		
Exhaust	200 Ø/mm	200 Ø/mm
DIMENSIONS		
Size HxWxD	1960×980×1190 mm	1960×980×1350 mm
Net weight (G,S)	310, 295, 315 kg	320, 310, 325 kg

