



PRIMUS DX55, 77, 90 TUMBLE DRYERS



MODELS:

DX55
DX77
DX90

DIMENSIONS:

HxWxD: 2175x1170x1270mm
HxWxD: 2390x1345x1315mm
HxWxD: 2390x1345x1505mm

CAPACITY:

55kg
77kg
90kg

IDEAL FOR:



HOSPITALITY



INDUSTRIAL

FEATURES:

- ▶ Gas, steam heating, electrical heating (DX55)
- ▶ Large door opening for easy loading and unloading (Ø 68cm)
- ▶ Galvanized Drum
- ▶ Radial airflow
- ▶ Standard reversing drum
- ▶ Self-cleaning lint screen
- ▶ Preheating of intake air

OPTIONS:

- ▶ Stainless steel drum
- ▶ Stainless steel front panel with black painted door
- ▶ Residual moisture control Sensodry+®:
 - lower energy and utility costs
 - lower linen replacement costs
- ▶ SafeTech™ Suppression System

CONTROL:

Dual Digital Control or OPL Micro

ONECARE^{cc} This machine is eligible for our all inclusive service solution, One Care.

		DX55	DX77	DX90
Capacity				
Maximum capacity	kg (lb)	55 (120)	77 (170)	90 (200)
Volume	litres	1020	1410	1660
Diameter	mm	1120	1290	1290
Airflow				
	l/s	660	1010	1010
Drying Average				
Gas heating	g/min	979	1401	1673
Electrical heating	g/min	698	-	-
Motors				
Fan	kW	1.1	1.1	1.1
Drive	kW	1.1	1.1	1.1
Gas Heating				
Gas connection	NPT	1"	1"	1"
Electrical connection		3x 200-240V/50-60Hz, 3x 440-480V/50-60Hz, 3x 380-415V/50-60Hz		
Energy	kW	79	116	125
	kBTU/h	270	395	425
Steam Heating				
Steam connection	NPT	3/4"		
Electrical connection		3x200-240V/50-60Hz, 3x440-480V/50-60Hz, 3x380-415V/50-60Hz		
High pressure 6.9 bar	kW	54.95	77.81	77.81
	kBTU/h	187.5	265.5	265.5
Electrical Heating				
Electrical connection		3x230-240V/50-60Hz 3x380V/50-60Hz 3x400-415V/50-60Hz 3x440V/50-60Hz 3x460-480V/50-60Hz	-	-
Energy	kW	60	-	-
Exhaust				
	mm	Ø 254	Ø 305	Ø 305
Dimensions				
HxWxD	mm	2175x1170x1270	2390x1345x1315	2390x1345x1505
Net weight (G,S)	kg	565, 555, 605	- , 635, 705	- , 705, 770
Transport Data				
Packed (foil E, G) HxWxD	mm	2290x1220x1820	2510x1320x1870	2510x1320x2070
Gross weight (foil, E, G,S)	kg	600, 585, 635	- , 670, 740	- , 740, 805
Packed (crate) HxWxD	mm	2310x1350x1890	2550x1530x1950	2550x1530x2140
Gross weight (crate, E, G, S)	kg	675, 660, 710	- , 755, 825	- , 825, 895

