



PRIMUS RXLINE WASHING MACHINES

MODELS:

RX80
RX105
RX135

DIMENSIONS:

HxWxD: 1115x660x785mm
HxWxD: 1225x750x785mm
HxWxD: 1225x750x900mm

CAPACITY:

9kg
12kg
15kg

IDEAL FOR:

	 INDUSTRIAL	 HOSPITALITY	 HEALTHCARE	 ANIMAL CARE	 EDUCATION	 PUBLIC SECTOR	 VENDED LAUNDRY
RX80	✓						
RX105	✓			✓			✓
RX135	✓			✓			✓

FEATURES:

- ▶ Rigid mounted, normal spin, up to 200G factor
- ▶ Stainless steel drum and tub
- ▶ Patented soap hopper
- ▶ Large drain valve (Ø 76 mm)
- ▶ Easy access to all vital parts from the front
- ▶ Large door opening for easy loading & unloading

OPTIONS:

- ▶ XControl - Fully programmable
- ▶ Stainless steel front and side panels
- ▶ USB plug (on the back panel)
- ▶ Prep for coin and Central Pay
- ▶ Liquid soap connection
- ▶ Liquid soap pumps
- ▶ Steam heating version
- ▶ Drain pump (RX80)
- ▶ ECO version: Lower kW rating on request
- ▶ 3rd water inlet

CONTROL:

- ▶ XControl FLEX (VEND) - fully programmable and customisable cycles
 - User-friendly screen with operating instructions built in as part of the control
 - Complete control content available in 34 languages
- ▶ XControl FLEX PLUS (OPL)
 - User-friendly screen with operating instructions built in as part of the control

ONECARE[∞] This machine is eligible for our all inclusive service solution, One Care.

RX LINE SPECIFICATIONS	RX80	RX105	RX135
Innerdrum			
Capacity 1:09	9kg / 18lbs	12kg / 26lbs	15kg / 33lbs
Capacity: 1:10	7,5kg / 16lbs	10,5kg / 23lbs	13,5kg / 30lbs
Volume			
Diameter	75l	105l	135l
	530 mm	620 mm	620 mm
Drum speed			
Wash	50 rpm	46 rpm	46 rpm
Extraction	820 rpm	760 rpm	760 rpm
G-Factor	200	200	200
Heating			
Electricity - very low-low-std-higher-special 1-2-3	3-4,6-6-9--7--	3---9-12-6-7--	3---12-13,8-6-7-9
Steam	1 - 8 bar	1 - 8 bar	1 - 8 bar
Hot water	90 °C	90 °C	90 °C
Sound pressure level	≤65 dB (A)	≤65 dB (A)	≤65 dB (A)
Water valves connection	3/4" BSP	3/4" BSP	3/4" BSP
Water pressure	100 - 800 kPa	100 - 800 kPa	100 - 800 kPa
Rec. water pressure	300 - 500 kPa	300 - 500 kPa	300 - 500 kPa
Water inlet	20 l/min	20 l/min	20 l/min
Drain valve	76 outer Ø mm	76 outer Ø mm	76 outer Ø mm
Flow amount with drain valve	210 l/min	210 l/min	210 l/min
Steam valve connection	1/2" BSP	1/2" BSP	1/2" BSP
Steam pressure	100 - 800 kPa	100 - 800 kPa	100 - 800 kPa
Transport Data			
Packed HxWxD	1115x660x785mm	1355x800x835mm	1355x800x950mm
Gross weight	145 kg	185 kg	200 kg

DIMENSIONS

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	P	Q	R	S
RX80	660	785	1115	676	349	166	88	920	1010	113	218	293	415	1020	1025	535	48	180
RX105	750	785	1225	676	342	225	98	1030	1120	113	218	338	505	1130	1135	480	42	192
RX135	750	900	1225	788	342	225	98	1030	1120	113	218	338	505	1130	1135	480	42	192

width depth height

