





SCHULTHESS TOPLINE 9240



DIMENSIONS: Height: 900mm Width: 630mm Depth: 720mm CAPACITY:

8kg





FEATURES:

- Large 4.3" colour display
- Drum vanes for 3D-Washing
- Drum capacity: 70 l
- Spin speed: 1600 rpm
- G Factor 690
- Residual moisture 43%
- Language selection button
- (23 languages)

- profiClean programme button
- USB-interface for PC software
- Drain valve or drain pump
- 94 profiClean and 24 freely programmable slots

OPTIONS:

- Drain valve or drain pump
- Anthracite or chrome steel finish
- Door hinge right or left
- Liquid detergent pumps

ONECARE^{∞} This machine is eligible for our all inclusive service solution, One Care.



This machine is compatible with our smart laundry solution, serviceMaster

THE COMMERCIAL LAUNDRY EXPERTS.



Model with drain pump (P)7720.1PUModel with drain valve (V)7720.1UVApplication features8kgLoad capacity601Spinning speed1500 rpmg Factor605gResidual moisture "44%Structural designr//wFooted appliance with work surface Door hinge"r//wDimensionsr//wHeight85cm 60cmUidth60cmDepth including distance from wall67cmDepth with door open (front loader)110cmHeight (adjustable)1cmVeight when empty90kgDatt1Detergent tank and drum Loading openingchrome-nickel steel 1.6mLording opening only model (P)1.5mPiran2.30 v 1N~ / 50Hz / 4.6kW 10AVoltage / connection fuse of vater connection1.5mPressure hose G 3" with fine filter1.5m- Con be connected to cold water hot water2.006/42/ECVictor Directive2.006/42/ECConforms to the Europeon Machinery Directive2.006/42/ECConforms to the Europeon Machinery Directive2.006/42/ECContry of origin GuaranteeSwitzerland Guarantee	STARLINE 7720 WASHING MACHINE		
Application featuresLoad capacity8kgDrum capacity601Spinning speed1500 rpmg Factor605gResidual moisture *44%Structural design.Footed appliance with work surface.Door hinge*r//wDimensions60cmWidth60cmDepth with door open (from talladder)10cmPepth with door open (from talladder)10cmHeight (adjustable)1cmVidth34cm / 180°Automatic door opening (ading opening)34cm / 180°Automatic door opening (any model (P))1.5mOnnerting cable1.5mPodel with drain valve (V)50mmFordiel with drain valve (V)30 v 1N~ / 50Hz / 4.6kW 10AVidte connection (fuser connected to cold water hot water 70°CPressure hose G3" with fine filter1.5m-Can be connected to cold water hot water 70°C-Can be connected to cold water hot watercold water/ hot water 70°C-Can be connected to cold water hot water2006/42/EC-Conforms to the European Machinery2006/42/EC-Contry of originSwitzerland-Country of originSwitzerlan	Model with drain pump (P)	7720.1PU	
Load capacity8kgDrum capacity601Spinning speed1500 rpmg Factor605gResidual moisture "44%Structural designFooted appliance with work surface-Door hinge"r//wDimensions-Height85cmWidth60cmDepth including distance from wall67cmDepth with door open (front loader)110cmHeight (adjustable)1cmWeight when empty90kgEduipment24cm / 180°Loading opening34cm / 180°Automatic door opening1.5mOnnecting cable1.5mPoter in hose with benda, only model (P)21mm- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectric connected loads fuse230 V 1N- / 50Hz / 4.6kW 10AVotage / connected loads fuse230 V 1N- / 50Hz / 2.3kW 10AVotare ronnection1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure1.10 barEuropeen Machinery Directive2006/42/ECConforms to the Europeen Machinery Directive2006/42/ECCountry of originSwitzerlandGuarantee1 year	Model with drain valve (V)	7720.1UV	
Drum capacity601Spinning speed1500 rpmg Factor605gResidual moisture "44%Structural designr//waStructural designFooted appliance with work surface- r//waDomensionsImage: Span and S	Application features		
Spinning speed1500 rpmg Factor605gResidual moisture 344%Structural design.Footed appliance with work surface.bonensionsr//wDimensions60cmDepth including distance from wall67cmDepth with door open (front loader)110cmHeight (adjustable)1cmWeight when empty90kgEdupment34cm / 180°Loading opening34cm / 180°Automatic door opening1.5mOrnin: Drain hose with benda, only model (P)1.5m- Model with drain pump (P)21mm- Model with drain pump (P)230 V 1N - / 50Hz / 4.6kW 10AVoltage / connection400 V 2N - / 50Hz / 4.6kW 10AVoltage / connected loads fuser230 V 1N - / 50Hz / 2.3kW 10AVoltage / connected loads vater hot water210 water/ hot water 70°C- Pressure hose G ¾" with fine filter1.5m- Ornin se with benda, only model (P)1.5m- Restrict power and water230 V 1N - / 50Hz / 2.3kW 10AVoltage / connected loads vater hot water2006/42/EC- Pressure hose G ¾" with fine filter2006/42/EC- Water pressure1-10 bar- Conforms to the European Machinery Directive2006/42/ECConforms to the Surger on direction2006/42/ECCountry of originSwitzerlandGuarantee1 year	Load capacity	8kg	
g Factor605gResidual moisture "44%Structural designFooted appliance with work surfaceDoor hinge"r//wDimensionsHeight85cmWidth60cmDepth including distance from wall67cmDepth with door open (front loader)110cmHeight (adjustable)1cmWeight when empty90kgEduipment34cm / 180°Loading opening34cm / 180°Automatic door opening1.5mOnnecting cable1.5mPorain hose with benda, only model (P)21mmModel with drain pump (P)21mmElectrical connection400 V 2N- / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N- / 50Hz / 2.3kW 10AVoltage / connected to cold water hot watercold water/hot water 70°C- Can be connected to cold water hot watercold water/hot water 70°C- Vater pressure1-10 barEluropean Machinery Directive2006/42/ECConforms to the European Machinery Directive2006/42/ECCountry of originSwitzerlandGuarantee1 year	Drum capacity	601	
Residual moisture ¹ 44% Structural design . Footed appliance with work surface . Door hinge ³ r/l/w Dimensions . Height 85cm Width 60cm Depth including distance from wall 67cm Depth with door open (front loader) 110cm Height (adjustable) 1cm Veight when empty 90kg Equipment . Deter gent tank and drum (chrome-nickel steel . Loading opening 34cm / 180° Automatic door opening . Automatic door opening 1.5m Onnecting cable 1.5m Prain hose with benda, only model (P) 21mm - Model with drain valve (V) 50mm Electrical connection 400 V 2N- / 50Hz / 4.6kW 10A Voltage / connected loads /fuse 230 V 1 N- / 50Hz / 2.3kW 10A /fuse	Spinning speed	1500 rpm	
Structural designFooted appliance with work surface Door hinge ³⁰ •Door hinge ³⁰ r/l/wDimensions85cm 60cmHeight85cm 60cmWidth60cmDepth including distance from wall67cmDepth with door open (front loader)110cmHeight (adjustable)1cmWeight when empty90kgEquipment34cm / 180°Loading opening Automatic door opening Onnecting cable1.6mDrain: Drain hose with benda, only model (P)1.5m- Model with drain pump (P) 21mm21mm- Model with drain valve (V)50mmElectric power and waters230 V 1 N- / 50Hz / 4.6kW 10AVoltage / connected to cold water hot water1.5m- Can be connected to cold water hot water2006/42/EC- Water pressure1-10 barSafety and service2006/42/ECConforms to the European Machinery Directive2006/42/ECCountry of originSwitzerlandGuarantee1 year	g Factor	605g	
Footed appliance with work surface Door hinge ³⁰ r/l/wDimensionsHeight Width85cm 60cmDepth including distance from wall67cmDepth with door open (front loader)110cmHeight (adjustable)1cmWeight when empty90kgEquipmentDetergent tank and drum Loading openingchrome-nickel steel 34cm / 180°Automatic door opening Connecting cable1.5mDrain hose with benda, only model (P)1.5mElectric Jonnection Voltage / connected loads (fuse400 V 2N- / 50Hz / 4.6kW 10AVoltage / connected loads (fuse1.5mConde with drain valve (V)300 V 1N- / 50Hz / 2.3kW 10AVoltage / connected to cold water hot water1.5mCond be connected to cold water hot water2006/42/ECConforms to the European Machinery Directive2006/42/ECConforms to the European Machinery Directive2006/42/ECCountry of origin GuaranteeSwitzerland	Residual moisture ¹⁾	44%	
work surface Door hinge ³⁰ · Dimensions r///w Dimensions 60cm Peight 85cm Width 60cm Depth including distance from wall 67cm Depth with door open (front loader) 110cm Height (adjustable) 1cm Weight when empty 90kg Equipment storm -nickel steel Loading opening 34cm / 180° Automatic door opening - Connecting cable 1.5m Drain 1.5m Porain hose with benda, only model (P) 21mm - Model with drain pump (P) 21mm - Model with drain valve (V) 50mm Electric power and water 230 V 1 N- / 50Hz / 4.6kW 10A Voltage / connected lo cold water hot water cold water/ hot water 70°C - Pressure hose G ¾" with fine filter 1.5m - Can be connected to cold water hot water cold water/ hot water 70°C - Votare pressure 1-10 bar - Can be connected to cold water hot water 2006/42/EC - Water pressure 2006/42/	Structural design		
DimensionsHeight85cmWidth60cmDepth including distance from wall67cmDepth with door open (front loader)110cmHeight (adjustable)1cmWeight when empty90kgEquipmentDetergent tank and drum Loading openingchrome-nickel steelLoading opening34cm / 180°Automatic door opening Connecting cable1.6mDrain Drain hose with benda, only model (P)21mm- Model with drain pump (P)21mmElectrical connection400 V 2N- / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N- / 50Hz / 2.3kW 10AVoltage / connected to cold water hot watercold water/ hot water 70°C- Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot water2006/42/EC- Water pressure2006/42/EC- Conforms to the European Machinery DirectiveSwitzerlandConforms to the European Machinery DirectiveSwitzerland		•	
Height85cmWidth60cmDepth including distance from wall67cmDepth with door open (front loader)110cmHeight (adjustable)1cmWeight when empty90kgEquipmentDetergent tank and drum Loading openingchrome-nickel steelLoading opening34cm / 180°Automatic door opening Connecting cable1.6mDrain2- Drain hose with benda, only model (P)21mm- Model with drain pump (P)21mmElectrical connection400 V 2N- / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N- / 50Hz / 2.3kW 10AVoltage / connected loads /fuse1.5mPressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure1-10 barConforms to the European Machinery Directive2006/42/ECConforms to the European Machinery DirectiveSwitzerland	Door hinge ³⁾	r/l/w	
Width60cmDepth including distance from wall67cmDepth with door open (front loader)110cmHeight (adjustable)1cmWeight when empty90kgEquipmentDetergent tank and drum Loading openingchrome-nickel steelLoading opening34cm / 180°Automatic door opening Connecting cable1.6mDrain- Drain hose with benda, only model (P)21mm- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectrical connection400 V 2N- / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N- / 50Hz / 2.3kW 10AWater connection1.5m- Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure1-10 barEfetry and service2006/42/ECConforms to the European Machinery DirectiveSwitzerlandGuarantee1 year	Dimensions		
Instruct from wall67cmDepth including distance from wall67cmDepth with door open (front loader)110cmHeight (adjustable)1cmWeight when empty90kgEquipmentDetergent tank and drum Loading openingchrome-nickel steelAutomatic door opening34cm / 180°Automatic door opening.Connecting cable1.6mDrain Drain hose with benda, only model (P)21mm- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectric power and water200 V 2N- / 50Hz / 4.6kW 10AVoltage / connected loads rfuse230 V 1 N- / 50Hz / 2.3kW 10AVater connection1.5m- Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure110 barErectric pressure2006/42/EC- Water pressure2006/42/EC- Surforms to the European Machinery DirectiveSwitzerland	-		
from wallordinPepth with door open (front loader)110cmHeight (adjustable)1cmWeight when empty90kgEquipment34cm / 180°Loading opening34cm / 180°Automatic door opening.Connecting cable1.6mDrain Drain hose with benda, only model (P)1.5m- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectric power and water support230 V 1 N~ / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N~ / 50Hz / 2.3kW 10A- Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/hot water 70°C- Water pressure1-10 barSafety and service2006/42/ECConforms to the European Machinery Directive2006/42/ECCountry of origin GuaranteeSwitzerland		60cm	
IntermIntermHeight (adjustable)1cmWeight when empty90kgEquipment34cm / 180°Loading opening34cm / 180°Automatic door opening.Automatic door opening1.6mConnecting cable1.6mDrain: Drain hose with benda, only model (P)21mm- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectrica connected loads /fuse230 V 1 N~ / 50 Hz / 4.6k W 10AVoltage / connected loads /fuse Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot water.Safety and service.Conforms to the European Machinery Directive.Conforms to the European Machinery Directive.Country of origin Guarantee.Switzerland Guarantee.	from wall	67cm	
Weight when empty90kgEquipmentDetergent tank and drumchrome-nickel steelLoading opening34cm / 180°Automatic door opening.Automatic door opening1.6mConnecting cable1.5mDrain: Drain hose with benda, only model (P)21mm- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectric power and water>400 V 2N- / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N- / 50Hz / 2.3kW 10AVater connection Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure110 barEncore to the guropean Machinery Directive2006/42/ECConforms to the European Machinery DirectiveSwitzerlandGuarantee1 year	(front loader)	110cm	
EquipmentDetergent tank and drumchrome-nickel steelLoading opening34cm / 180°Automatic door opening•Automatic door opening1.6mDrain: Drain hose with benda, only model (P)1.5m- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectric power and water supplyElectrical connected loads /fuse400 V 2N- / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N- / 50Hz / 2.3kW 10AVater connection Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure1-10 barSafety and service2006/42/ECConforms to the European Machinery Directive2006/42/ECCountry of origin GuaranteeSwitzerlandGuarantee1 year			
Detergent tank and drumchrome-nickel steelLoading opening34cm / 180°Automatic door opening.Connecting cable1.6mDrain: Drain hose with benda, only model (P)1.5m- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectric power and water byElectrical connection400 V 2N~ / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N~ / 50Hz / 2.3kW 10APressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°CWater pressure1.10 barSafety and service2006/42/ECConforms to the European Machinery Directive2006/42/ECGuarantee1 year	0 1 7	90kg	
Loading opening34cm / 180°Automatic door opening-Connecting cable1.6mDrain Drain hose with benda, only model (P)15m- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectric power and waterFlextrical connection400 V 2N- / 50 Hz / 4.6k W 10AVoltage / connected loads fine filter300 V 1N- / 50 Hz / 2.3k W 10AOvater connection Pressure hose G ¾" with nie filter1.5m- Can be connected to cold water pressurecold water/ hot water 70°C- Water pressure110 bar- Safety and service-Conforms to the pirectiveSwitzerlandCountry of originSwitzerlandGuarantee1 year	Equipment		
Automatic door opening Connecting cable.Drain: Drain hose with benda, only model (P)1.5m- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectric power and water subscriptionElectrical connection400 V 2N~ / 50Hz / 4.6kW 10AVoltage / connected loads fine filter230 V 1 N~ / 50Hz / 2.3kW 10A- Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure110 barSafety and service2006/42/ECConforms to the European Machinery DirectiveSwitzerlandGuarantee1 year	Detergent tank and drum	chrome-nickel steel	
Connecting cable1.6mDrain: Drain hose with benda, only model (P)1.5m- Model with drain pump (P)21mm- Model with drain valve (V)50mm- Model with drain valve (V)50mmElectrica connection400 V 2N~ / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N~ / 50Hz / 2.3kW 10AWater connection Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure110 barSafety and service2006/42/ECConforms to the European Machinery DirectiveSwitzerlandGuarantee1 year	Loading opening	34cm / 180°	
DrainImport Service- Drain hose with benda, only model (P)1.5m- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectric power and waterElectrical connection400 V 2N - / 50 Hz / 4.6k W 10AVoltage / connected loads /fuse230 V 1 N - / 50 Hz / 2.3k W 10AWater connection Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure110 barSafety and service-Conforms to the European Machinery DirectiveSwitzerlandCountry of originSwitzerlandGuarantee1 year		•	
Drain hose with benda, only model (P)1.5m- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectric power and water with of the second sec		1.6m	
only model (P)1.5m- Model with drain pump (P)21mm- Model with drain valve (V)50mmElectric power and water vplyElectrical connection400 V 2N~ / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N~ / 50Hz / 2.3kW 10AWater connection Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure1-10 barSafety and service2006/42/ECConforms to the European Machinery DirectiveSwitzerlandGuarantee1 year			
- Model with drain valve (V)50mmElectrica power and water >>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>		1.5m	
Electric power and water suplyElectrical connection400 V 2N~ / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N~ / 50Hz / 2.3kW 10AWater connection Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure1-10 bar2006/42/ECConforms to the European Machinery Directive2006/42/ECCountry of originSwitzerlandGuarantee1 year	- Model with drain pump (P)	21mm	
Electrical connection400 V 2N~ / 50Hz / 4.6kW 10AVoltage / connected loads /fuse230 V 1 N~ / 50Hz / 2.3kW 10AWater connection Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure1-10 barSafety and serviceConforms to the European Machinery Directive2006/42/ECCountry of originSwitzerlandGuarantee1 year	- Model with drain valve (V)	50mm	
Voltage / connected loads /fuse230 V1 N~ / 50 Hz / 2.3kW 10AWater connection Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot water?cold water/ hot water 70°C- Water pressure1-10 barSafety and serviceConforms to the European Machinery Directive2006/42/ECCountry of originSwitzerlandGuarantee1 year	Electric power and water s	upply	
/fuse230 V TN~7 SOH2 / 2.3kW IOA/fuse230 V TN~7 SOH2 / 2.3kW IOAWater connection Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure1-10 barSafety and service2006/42/ECConforms to the European Machinery Directive2006/42/ECCountry of originSwitzerlandGuarantee1 year	Electrical connection	400 V 2N~ / 50Hz / 4.6kW 10A	
- Pressure hose G ¾" with fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure1-10 barSafety and service2006/42/ECConforms to the European Machinery Directive2006/42/ECCountry of origin GuaranteeSwitzerlandGuarantee1 year		230 V 1 N~ / 50Hz / 2.3kW 10A	
fine filter1.5m- Can be connected to cold water hot watercold water/ hot water 70°C- Water pressure1-10 bar- Water pressure2006/42/ECConforms to the European Machinery DirectiveSwitzerlandCountry of originSwitzerlandGuarantee1 year	Water connection		
water hot watercold water/ hot water /0°C- Water pressure1-10 barSafety and service2006/42/ECConforms to the European Machinery Directive2006/42/ECCountry of origin GuaranteeSwitzerland 1 year		1.5m	
- Water pressure1-10 barSafety and service2006/42/ECConforms to the European Machinery Directive2006/42/ECCountry of originSwitzerlandGuarantee1 year		cold water/ hot water 70°C	
Safety and serviceConforms to the European Machinery2006/42/ECDirective2006/42/ECCountry of originSwitzerlandGuarantee1 year		1-10 bar	
Conforms to the European Machinery Directive2006/42/ECCountry of originSwitzerlandGuarantee1 year	Safety and service		
Guarantee 1 year	Conforms to the European Machinery	2006/42/EC	
,	Country of origin	Switzerland	
Service by Schulthess Maschinen AG		1 year	
	Service by	Schulthess Maschinen AG	







SCHULTHESS TOPLINE

~~~

MODELS:	DIMENSIONS:	CAPACITY:
TA 9340	HxWxD: 900x630x830mm	8kg
TC 9350	HxWxD: 900x630x840mm	
TW 9360	HxWxD: 900x630x840mm	

IDEAL FOR:

M INDUSTRIAL	
HEALTHCARE	E VENDED LAUNDRY
ANIMAL CARE	

FEATURES:

- Load capacity: 8 kg
- Large 4.3" colour display
- Drum capacity: 150 l
- LED drum lighting
- Residual moisture measurement
- Language selection button
- Electronically and time
- controlled drying programmes

OPTIONS:

- Exhaust air system (TA 9340)
- Condensation system (TC 9350)
 Condensation system with heat
- pump (TW 9360)
 Anthractite or chrome steel finish
- Door hinge right or left

 $ONECARE^{cc}$ This machine is eligible for our all inclusive service solution, One Care.



This machine is compatible with our smart laundry solution, serviceMaster

THE COMMERCIAL LAUNDRY EXPERTS.

TOPLINE PRO 9240		
Model with drain pump (P)	9240.1EPU	
Model with drain valve (V)	9240.1EUV	
Application features		
Load capacity	8kg	
Drum capacity		
Spinning speed	•	
g factor	•	
Residual moisture 1)	r/l/w	
Structural design		
Footed appliance with work surface	•	
Door hinge 2)	r/l/w	
Dimensions		
Height	90cm	
Width	63cm	
Depth including distance from wall	72cm	
Depth with door open (front loader)	116cm	
Height (adjustable)	1cm	
Weight when empty	102kg	
Equipment		
Detergent tank and drum	chrome-nickel steel	
Loading opening	34 / 180°	
Automatic door opening	•	
Connecting cable	1,6cm	
Drain		
– Drain hose with benda, only model (P)	1,5m	
Model with drain pump (P)	21mm	
Model with drain valve (V)	50mm	
Electric power and water supply		
Voltage / connected loads / fuse	400 V 3 N~ / 50Hz / 4,6kW / 10A 400 V 2 N~ / 50Hz / 4,6kW / 10A 230 V 1 N~ / 50Hz / 2,5kW / 13A 230 V 1 N~ / 50Hz / 2,3kW / 10A	
Water connection		
Pressure hose G ¾" with fine filter	1,5m	
Can be connected to cold water / hot water	cold water / hot water 70 °C	
Water pressure	1–10 bar	
Safety and service		
Conforms to the European Machinery Directive	2006/42/EC	
Country of origin	Switzerland	
Guarantee	1 year	
Service by	Schulthess Maschinen AG	
Name and address of supplier	Schulthess Maschinen AG, CH-8633 Wolfhausen/ZH	