

Maytag MDE/MDG28PD

Commercial Coin-Op Tumble Dryer



MICROPROCESSOR CONTROLS

- Provides simple programming options for owner: including adjustable cycle price, cycle time, diagnostics and vend count.
- Easy one-touch cycle selection for customers.

TURBOVENT DRYER TECHNOLOGY

- Additional blower wheel provides exceptional performance in long vents.
- High airflow reduces dry time.

PORCELAIN-ENAMEL TOP

- Durable finish for high-use environments.

MAYTAG CONNECT 360 COMPATIBLE

- Delivers real-time machine diagnostic to any tablet, computer or smartphone via the cloud. Management and feedback features offer owners the ultimate in machine control keeping you informed regarding pricing, service and diagnosis from anywhere you have access to the internet.



SIMPLE PROGRAMMING



FRONT ACCESS PANEL



ONE-TOUCH CYCLE SELECTION



MATCHING WASHER AVAILABLE

MAYTAG'S COMMITMENT TO DEPENDABLE QUALITY

For well over 50 years, Maytag® Commercial Laundry has promised and delivered dependability. We create that quality by making durable washers and dryers, built to endure heavy use and last for years. We design our machines to perform reliably and to produce consistent results. Finally, we give our washers and dryers the power to do their jobs thoroughly, cleaning and drying laundry quickly and efficiently—and justifying the trust that has been placed in us for generations.



MAYTAG MDE/MDG28PD COMMERCIAL DRYER

COIN-OP / MANUAL

DRYER SPECIFICATIONS	
EXPORT MODEL	MDE/MDG28PD
Motor	
Single-phase, thermoprotected against overload, auto reset	Yes
HP (kw)	1/2 (.25)
Tumble speed - RPM	50 + 1
CAPACITY	
Cu ft. (litres)	6.7 (190)
AIRFLOW	
Gas models - cfm (cmm)	230 (6.5)
Electric models - cfm (cmm)	215 (6.1)
SOUND LEVEL	
Sound pressure level, Lpa (dba)	58
ELECTRICAL REQUIREMENTS (V)	220-240v/50Hz
BREAKER/FUSE	
MDE export model - amps	25
MDG export model - amps	10
ELECTRIC HEATING ELEMENT	
Watts	4,600
GAS RATING	
MDG Model - BTU/hr (kcal/hr.)	20,000 (5,040)
EXHAUST DUCT DIAMETER - IN (mm)	4 (100)*
ELECTRONIC BURNER IGNITION	
MDG model	Yes
GAS INLET	
MDG Model - inch	3/8 N.P.T
ADJUSTABLE LEVELING LEGS	Yes
APPROXIMATE WEIGHT	
Crated - lbs. (kg) electric/gas	160 (73)/113 (74)
Uncrated - lbs. (kg) electric/gas	147 (67)/150 (68)
DIMENSIONS	
Width-in (mm)	27 (686)
Depth-in (mm)	29 (737)
Height-in (mm)	45.75 (1,162)
Door opening diameter-in(mm)	18.25 (464)
OPTIONAL PLINTH ADDS	
Height-in (mm)	2.75 (70)
*Use 4" (100 mm) diameter rigid aluminum or galvanized steel duct. Never use plastic, non-metal or combustible duct. **Includes height of metercase. See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.	

MAXIMUM EXHAUST DUCT LENGTH PER NUMBER OF TURNS

Number Of 90° Turns	Rigid Metal Vent	
	Box Hood and Louvered Style	Angled Hood Style
0	135 ft. (41.2 m)	129 ft. (39.3 m)
1	125 ft. (38.1 m)	119 ft. (36.3 m)
2	115 ft. (35.1 m)	109 ft. (33.2 m)
3	106 ft. (32.3 m)	100 ft. (30.5 m)
4	98 ft. (29.9 m)	92 ft. (28.0 m)

Number Of 90° Turns	Flexible Metal Vent	
	Box Hood and Louvered Style	Angled Hood Style
0	76 ft. (23.2 m)	62 ft. (18.9 m)
1	71 ft. (21.6 m)	57 ft. (17.4 m)
2	67 ft. (20.4 m)	53 ft. (16.2 m)
3	65 ft. (19.8 m)	51 ft. (15.6 m)
4	63 ft. (19.2 m)	49 ft. (14.9 m)

