

DX25
25KG
55LB

DX34
34KG
75LB

Primus DX Range

Tumble Dryer



KEY FEATURES

- Controls:
 - Dual Digital Control or OPL Micro
 - Coin operated version: XQ-Control
- Electrical, Gas and Steam heating
- Large door opening for easy loading and unloading (Ø 68cm).
- Galvanized drum
- Radial airflow
- Large lint filter

OPTIONS

- Stainless steel drum
- Stainless steel front panel with black painted door
- Coin operated version
- Reversing drum
- Residual moisture control Sensodry+® (only with Full OPL Micro):
 - lower energy and utility costs
 - lower linen replacement costs
- SafeTech™ Fire Suppression System



FAST DRYING



EASY OPERATION



SERVICE
FRIENDLY

WOLF

0800 840 9598
www.wolflaundry.co.uk

PRIMUS DX RANGE

TYPE		DX25	DX34
CAPACITY			
Maximum capacity	kg (lb)	25 (55)	34 (75)
Volume	litres	530	634
Diameter	mm	940	940
AIRFLOW	l/s	330	380 (G 330)
DRYING AVERAGE			
Gas heating	g/min	476	571
Electrical heating	g/min	390	521
MOTORS			
Fan	kW	0.4	0.4
Drive	kW	0.4	0.4
GAS HEATING			
Gas connection	NPT	1/2"	1/2"
Electrical connection		1×100-120V/50-60Hz, 1-3×200-240V/50-60 Hz 3×440-480V/50-60Hz, 3×380-415V/50-60Hz	
Energy	kW	38.1	48.4
	kBTU/h	130	165
STEAM HEATING			
Steam connection	NPT	3/4"	
Electrical connection		1×100-120V/50-60Hz, 1-3×200-240V/50-60 Hz 3×440-480V/50-60Hz, 3×380-415V/50-60Hz	
High pressure 6.9 bar	kW	33.29	39.24
	kBTU/h	113.6	113.9
ELECTRICAL HEATING			
Electrical connection		1×200-208V/50-60Hz, 3×200-208V/50-60Hz, 1x 230-240V/50-60Hz, 3x 230-240V/50-60Hz, 3x 380V/50-60Hz, 3x400-415V/50-60Hz, 3x 440V/50-60Hz, 3x 460-480V/50-60Hz	
Energy	kW	30	36
EXHAUST	mm	Ø 200	
DIMENSIONS			
HxWxD	mm	1960×980×1190	1960×980×1350
Net weight (G,S)	kg	310, 295, 315	320, 310, 325
TRANSPORT DATA			
Packed (foil E, G) HxWxD	mm	2060×1050×1270	2060×1050×1420
Packed (foil S) HxWxD	mm	2120×1050×1270	2120×1050×1420
Gross weight (foil, E, G,S)	kg	330, 320, 335	340, 330, 350
Packed (crate) HxWxD	mm	2240×1170×1350	2240×1170×1500
Gross weight (crate, E, G, S)	kg	395, 380, 400	410, 395, 415

