

S100.20	S100.25	S140.25
1M	1M	1.4M
20CM	25CM	25CM

Schulthess S Range

Professional Rotary Ironers



1. Reduced Utilities Costs

The electronic temperature control system, matched with a newly designed heat distribution system, have drastically cut the electric consumption of Schulthess 1000 and 1200, which feature the lightest footprint in the industry.

2. Chromed Steel Chest

Chromed steel has proven to be the best possible choice for ironing: it ensures an excellent resistance to friction and an extreme longevity.

3. Work Comfortably with Automatic Chest Movement

Work comfortably with Schulthess 1000 and 1200! With just a light pressure on the foot pedal you can start or stop the roller rotation, as well as open or close the chest to better feed your linen. Chest movement and roller rotation are controlled by an electric motor.

4. Practical Foot Pedal

Stops the roller rotation and leaves your hands free to accommodate the linen in the feeding process.

5. Electronic Temperature Control

The best and most accurate temperature control system available. Temperature can be freely adjusted by 1°C to perfectly suit the fabric type processed.

6. User Friendly Control Panel

Large, simple and extremely easy to understand.

7. Aluminium Feeding Table

Feeding your linen has become simpler thanks to the purposely shaped feeding profile. Aluminium surface can be easily cleaned and will grant the hygiene of your laundry.

8. Low-Cost Maintenance

Simple and reliable construction, matched with the small number of components, will grant the lowest maintenance costs.

WOLF

0800 840 9598
www.wolflaundry.co.uk

SCHULTHESS S RANGE



	S100.20	S100.25	S140.25
Roller dimensions	1000 x Ø 200 mm	1000 x Ø 250 mm	1000 x Ø 250 mm
Supply tension *	230V / 1 / 50Hz 415V / 3N / 50Hz	230V / 1 / 50Hz 415V / 3N / 50Hz	230V / 1 / 50Hz 415V / 3N / 50Hz
Heating power	3.6 kW	6.9 kW	7.5 kW
Motor	0,18 kW	0,18 kW	0,18 kW
Absorption (Amps)	230V / 1 : 13A 415V / 3 : 6A	400V / 3 : 10.5	400V / 3 : 10.5
Ironing speed	3.4 m / min	3.4 m / min	3,8 m / min
Ironing speed, variable	1 - 5 m/min	1 - 5 m/min	1 - 5 m/min
Steam extraction	n/a	n/a	option Ø70 mm, 30 m ³ /h
Feeding basin	option	option	option
Hourly production (recommended moisture)	20kg (15%)	25kg (15%)	35 kg (15-20%)
Ironer dimensions (wxdxh)	1305 x 420 x 933 mm	1505 x 420 x 933 mm	1840 x 420 x 1003 mm
Packing dimensions, crated (wxdxh)	1450 x 550 x 1120 mm	1650 x 550 x 1120 mm	2090 x 590 x 1250 mm
Weight, gross/net	85.5 / 74 kg	93 / 80.5 kg	106 / 146 kg

* DIFFERENT VOLTAGES THAN INDICATED AVAILABLE ON REQUEST