

Smeg UD512DSUK

Commercial Undercounter Dishwasher



KEY FEATURES

- Double skinned construction
- Double basket capability
- Electronic soft touch controls
- WRAS approved
- Auto-dosing chemical
- Wash pump with “soft start”
- Thermostop controlled rinse temperature
- Insulated boiler
- Auto-start function via door closure
- Atmospheric boiler and rinse pump (HTR)

TECHNICAL DATA

UD512DSUK

Cycle time	1 minute
Baskets (x2)	500 x 500 mm
Height	820 mm
Width	600 mm
Depth	600 mm
Baskets per hour	120 / 80 / 48 / 40
Number of programmes	7
Thermo-acoustic insulation	Door and wash chamber
Rinse aid dispenser	Peristaltic pump with electronic adjustment
Detergent dispenser	Peristaltic pump with electronic adjustment
Wash tank capacity	11L
Boiler capacity	6L
Boiler element	5kW 1ph / 5kW 3ph / 3.3kW 1ph / 1.7kW 1ph
Wash tank heating element	2.0kW
Power supply / Total power installed	1ph 5.7kW 25A / 3ph 5.7kW 16A / 1ph 4kW 20A / 1ph 2.7kW 13A
Wash pump	0.7kW
Water consumption per cycle	2.7L
Weight (net/gross)	68kg/76kg
Adjustable feet	Yes
Water connection	3/4" BSP
Useable loading height	415mm
Inlet water max temperature	60 °C